

field name req'd description JSON data type unique field identifier (primary & calculated) example DS00 header This JSON data submission should be populated with the project (not contract) data. A valid JSON file contains the header data documented on this page, and one data set specified in the following pages. description A complete monthly PARS submission consists of several JSON files inside a zip file, and should include DS01 to DS07, and optionally include DS08 to DS22. A correctly formatted PARS JSON Upload should consist of a zip file file named with the PARSID and CPP status date, for example: 1026_2023-07-28.zip. This zip file should contain JSON files with the DS number and title, for example: DS01_WBS.json DS07_IMPR_header.json Within each JSON file, PARSID and CPP_status_date should be identical, and match the zip file name. Technical documentation of the PARS JSON Schema format can be found here.
Valid data sets documented in this DID include:

• DS00 header

• DS01 WBS

• DS02 OBS • DSU1 WBS
• DS02 OBS
• DS03 cost
• DS03 cost
• DS04 schedule | ogic
• DS06 schedule | resources
• DS07 schedule | resources
• DS07 iPMR_header
• DS08 WAD
• DS09 CC | og
• DS10 CC | og detail
• DS11 variance
• DS12 variance _ CAL
• DS13 subK
• DS14 HDV_Cl
• DS15 risk_register
• DS16 risk_register | tasks
• DS17 WBS_EU
• DS18 schedule_calendar_std
• DS20 schedule_calendar_exception
• DS21 rates
• DS22 financial_calendar PARS ID PARS identifier for the project for which data is submitted. string, maxLength: 4, numerical PARS ID 3021 Contractor data-as-of-date. Align with DS22. CPP status date string, must be date as YYYY-MM-DD 2022-08-21 CPP_status_date CPP-1 CPP status_date = prior CPP_status_date CPP-2.CPP_status_date = prior 2nd CPP_status_date CPP-5.CPP_status_date = prior 5th CPP_status_date CPP-1.CPP_status_date = next CPP_status_date CPP-12.CPP_status_date = prior 12th CPP_status_date string, URL of PARS JSON Schema Version Specify the version of the JSON schema against which this data submission was prepared. \$schema \$schema https://json.pars.doe.gov/pars-cpp-json-schema-v5-0-0.json v02.00, 2022-08-19, PM-30, Melvin Frank, Updated for 1st release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release. revision



field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
DS01 WBS			
description		This data set should be populated with the project's contractor WBS identifiers for the entire span of the project (not the contract). Provide the contractor WBS identifiers in a hierarchical structure from the project (not the contract) level to the CA WBS level and to the WP and PP WBS levels. The data set should include all WBS identifiers in all other DSs in the same format. The data should align with dollarized RAM identifying intersections of CA WBS and OBS types.	
WBS ID	Х	Unique contractor WBS identifier. DS01.WBS ID	string, maxLength: 50 W001.42.27.02
title	Х	Unique WBS identifier title. DS01.title	string, maxLength: 255 Testing/Surveillance Improvements
level	X	WBS identifier hierarchical level relative to the project. The data is > 0, starting with 1 and increments by 1. The dataset should have only one level 1 WBS identifier that represents the entire project. DS01.level	integer, min. value: 1, max. value: 20
parent_WBS_ID		WBS identifier of the immediate hierarchical parent. Required unless DS01.level = 1. DS01.parent_WBS_ID	string, maxLength: 150 1.42.27
type	X	WBS type selection: WBS = summary level • SLPP = summary level planning package (assigned to project manager not to a CAM; thus, is not a CA and does not have any WP, PP, or lower DS01.WBS_level • CA = control account • PP = planning package • WP = work package MR, UB, contingency, and SM tasks should be associated with DS01.type = WBS. Should be set to PP or SLPP if DS03.EVT = K. BCWS, BCWP, ACWP, and ETC are roll-ups where DS01.type = CA or WBS. BCWS, BCWP, ACWP, and ETC are accounted for where DS01.type = WP or PP. While not preferred, ACWP may be collected at the CA level, i.e. where DS01.type = CA. However, the level ACWP is collected must be uniform across the dataset, i.e., all at CA or all at WP.	string, select from: WBS, SLPP, CA, PI
OBS_ID		Unique contractor OBS identifier that should be aligned with the associated CA and DS02.OBS. If DS01.type is above the CA, associate to the higher level OBS identifier. DS01.OBS ID	string, maxLength: 50 SC.CMCS.1.4.1
CAM		CAM selection: CAM name for DS01.type = CA, WP, PP. Project manager name for DS01.type = SLPP. Project or appropriate manager name for DS01.type = WBS. Format: [last name] space [first name] space [middle initial, optional].	string, maxLength: 100 Whitney Zachary B
WPM		WP manager. Required if DS01.type is WP or PP. Format: [last name] space [first name] space [middle initial, optional].	string, maxLength: 100 Guitierez Jose
subproject_ID		Unique subproject identifier aligned with DS04.subproject_ID. Required if DS01.WBS_external = Y. DS01.subproject_ID	string, maxLength: 50
IMP_ID		Unique IMP identifier. DS01.IMP ID	string, maxLength: 50
external	Х	WBS is external to the project (Y or N). DS01.external	string, select from: Y, N
exit_criteria		Criteria to determine completion of the WBS scope. Required if DS01.type = CA or SLPP. Provide if available for DS01.type = WBS, WP, or PP. DS01.exit_criteria	string, maxLength: 3000
narrative	Х	WBS identifier description from the EVMS cost tool; the scope statement or a short paragraph based on the WBS dictionary and aligned with DS08.narrative. Align with DS08.narrative.	string, maxLength: 3000 Testing/Surveillance Improvements
K_ref		DS01.narrative Contractual basis: contract number, section(s), and paragraph(s). Align with DS07.K_ID.	string, maxLength: 3000



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
BWC_ID		Unique base work construct identifier. Level 3 BWC where DS01.type = SLPP, WP, or PP. Level 2 and 3 BWC: • W.01 support • W.01.02 project • W.01.02 closeout • W.01.03 operations • W.02 engineering • W.02.01 R&D • W.02.02 conceptual • W.02.02 preliminary • W.02.04 final • W.02.05 general • W.03 procurement • W.03.01 qeneral • W.04 construction • W.04.01 engineering support • W.04.02 demolition • W.04.03 site preparation • W.04.03 site preparation • W.04.04 construction • W.05.01 SU • W.05.02 cold cx • W.05.03 hot cx	string, select from: W.01.01 project, W.01.02 closeout, W.01.03 operations, W.02.01 R&D, W.02.02 conceptual, W.02.03 preliminary, W.02.04 final, W.02.05 general, W.03.01 general, W.04.01 engineering support, W.04.02 demolition, W.04.03 site preparation, W.04.04 construction, W.05.01 SU, W.05.02 cold cx, W.05.03 hot cx
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
02 OBS			1
escription		This data set should be populated with the project's contractor functionally-based OBS identifiers for the entire span of the project (not the contract). Provide the contractor OBS identifiers in a hierarchical structure from the project level to the CA WBS level. The data should include all OBS identifiers in all other DSs in the same format. The data should align with dollarized RAM identifying intersections of CA WBS and OBS types.	
BS ID	Х	Unique contractor OBS identifier.	string, maxLength: 50
		DS02.OBS_ID	MB.FC.4.2.82
tle	Х	Unique OBS identifier title.	string, maxLength: 255
		DS02.title	Payroll & Benefits Accounting, Workforce Planning
evel	Х	OBS identifier hierarchical level relative to the project. The data is > 0, starting with 1 and increments of 1. The data should have only one level 1 OBS identifier, the OBS identifier representing the head of the contractor.	integer, min. value: 1, max. value:
		DS02.level	
arent_OBS_ID		OBS identifier of the immediate hierarchical parent. Required unless DS02.level = 1.	string, maxLength: 50
		DS02.parent_OBS_ID	MB.FC.4.2.82
xternal	Х	OBS is external to the project (Y or N).	string, select from: Y, N
		DS02.external	
arrative		OBS identifier description from the EVMS cost tool. A short paragraph based on the functional OBS. Align with DS08.narrative.	string, maxLength: 3000
		DS02.narrative	
evision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS03 cost			
description		This data set should be populated with the project's contractor EVMS cost tool time-phased data for the entire span of the project (not the contract). Provide the contractor EVMS cost tool time-phased data at the WP and PP WBS level by EOC. The data should be provided at the WP, PP, and SLPP WBS levels only with one period date/WBS_ID_WP/EOC record; however, provide at CA WBS level for only those CAs where ACWP (DS03.ACWPi_dollars and DS03.ACWPi_units) is reported for entire project.	
period date	Х	Time-phased period end dates. The data should align with the the CPP_status_dates, and not change during the span of the project. DS03.period_date	string, must be date as YYYY-MM-DD 2020-01-01
WBS_ID_WP		WP or PP WBS identifier if DS01.type = WP or PP.	string, maxLength: 150
		DS03.WBS_ID_WP CPP-1.DS03.WBS_ID_WP = prior CPP_status_date	1.42.27.2
WBS_ID_CA	Х	Unique contractor WBS identifier for following:	string, maxLength: 150 1.42.27.2
		CPP-1.DS03.WBS_ID_CA = prior CPP_status_date	
EOC	X	EOC selection: labor material subcontract ODC indirect (may be used after coordination with PM. To consist only of indirect costs.)	string, select from: labor, material, subcontract, ODC, indirect
		DS03.EOC	
EVI		EVT selection that should be aligned with DS04.EVT (provide explanations in DS03,justification_EVT): **A = LOE** **B = weighted milestones (explain if utilized)* **C = percent complete or for use in DS03, discrete (combination of discrete DS03.EVT* **D = units complete** **E = 50-50** **F = 0-100** **G = 100-0 (explain if utilized)* **H = variation of 50-50 (explain if utilized)* **H = variation of 50-50 (explain if utilized)* **K = planning package (overrides where DS01.type = PP or SLPP)* **L = assignment percent complete (explain if utilized)* **M = calculated apportionment (explain if utilized)* **N = steps (explain if utilized)* **O = earned as spent (explain if utilized)* **O = earned as spent (explain if utilized)* **N = only for DS01.type = CA where ACWP is reported for the entire project. Discrete EVTs for metrics consists of B, C, D, E, F, G, H, L, N, O, P. Required if DS01.type = WP, PP, or SLPP.	string, select from: A, B, C, D, E, F, G, H, J, K, L, M, N, O, P, NA
justification_EVT		Justification narrative where DS03.EVT = B, G, H, J, L, M, N, O, or P. DS03.justification_EVT	string
EVT_J_to_WBS_ID		DS03.WBS_ID_WP apportioned to, if DS03.EVT = J or M. DS03.EVT_J_to_WBS_ID	string
EVT_J_pct		Percent apportioned, if apportioned from another DS03.WBS_ID_WP. DS03.EVT_J_pct	number, max. of 2 decimal places
BCWSi_dollars	Х	BCWS incremental (dollars). DS03.BCWSi_dollars DS03.BCWSc = cumulative DS03.DB = totalRP + 1 CPP-1,DS03.BCWSi_dollars = prior CPP_status_date, next period_date CPP-1,2.DS03.BCWSc,DB,BCWSi_dollars = prior 1st,2nd CPP_status_date	number, max. of 2 decimal places 11234.09, 355651.29
BCWPi_dollars	X	BCWP incremental (dollars). DS03.BCWPi_dollars DS03.BCWPc = cumulative CPP-1,2_DS03.BCWPc,BCWPi_dollars = prior 1st,2nd CPP_status_date	number, max. of 2 decimal places 11234.09, 355651.29



field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
ACWPi_dollars	Х	ACWP incremental (dollars).	number, max. of 2 decimal places
CWF1_uollars	^	DS03.ACWPi_dollars	11234.09, 355651.29
		DS03.ACWPc = cumulative	
		CPP-1,2_DS03.ACWPc,ACWPi_dollars = prior 1st,2nd CPP_status_date	
TCi_dollars	Х	ETC incremental (dollars).	number, max. of 2 decimal places
		DS03.ETCi_dollars	11234.09, 355651.29
		DS03.ETCc = cumulative	
s indirect		Represents indirect costs only (Y or N)? N if record is direct costs only. Omit this field if costs include both direct and indirect costs.	string, select from: Y, N
		DS03.is_indirect	
BCWSi_hours	Х	BCWS incremental (hours) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.BCWSi_hours	128.6, 45.3, 80.75
		DS03.DB = total	
BCWPi_hours	Х	BCWP incremental (hours) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.BCWPi_hours	128.6, 45.3, 80.75
		DS03.BCWPc = cumulative	
ACWPi_hours	X	ACWP incremental (hours) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.ACWPi_hours	128.6, 45.3, 80.75
ETCi_hours	Х	ETC incremental (hours) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.ETCi_hours	128.6, 45.3, 80.75
BCWSi_FTEs	Х	BCWS incremental (FTE) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.BCWSi_FTEs	
BCWPi_FTEs	Х	BCWP incremental (FTE) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.BCWPi_FTEs	
ACWPi_FTEs	Х	ACWP incremental (FTE) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.ACWPi_FTEs	
ETCi_FTEs	Х	ETC incremental (FTE) where DS03.EOC = labor only.	number, max. of 2 decimal places
		DS03.ETCi_FTEs	
CV_rpg	Х	Reprogramming CV. Reprogramming adjustment, cost variance.	number, max. of 2 decimal places
		DS03.CV_rpg	
SV_rpg	Х	Reprogramming SV. Reprogramming adjustment, schedule variance.	number, max. of 2 decimal places
		DS03.SV_rpg	
BAC_rpg	Х	Reprogramming BAC. Reprogramming adjustment, DB variance.	number, max. of 2 decimal places
		DS03.BAC_rpg	
CC_ID		Charge code identifier.	string, maxLength: 50
		DS03.CC_ID	MB.FC.4.2.82, MB.WC.1.4.1, MB.WC.1.8.1, SC.CMCS.1.4.1
CC_description		Charge code description.	string, maxLength: 3000
		DS03.CC_description	Payroll & Benefits Accounting, Workforce Planning
revision		V01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-79, PM-30, Melvin Frank, Updated for release. v03.21, 2022-11-79, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
S04 schedule			
description		This data set should be populated with the project's contractor BL and FC IMS tool data for the entire span of the project (not the contract). Provide the contractor BL and FC IMS tool data by task. There should be alignment between the BL and FC IMSs.	
schedule type	Х	Schedule type selection: • BL = baseline • FC = forecast The data should be scheduled by the schedule tool.	string, select from: BL, FC
		DS04.schedule_type	
		CPP-1.schedule_type = prior CPP_status_date	
task ID	Χ	Task identifier.	string, maxLength: 50
		DS04.task_ID	AHBL1190, TASK-1, TASK-2, TASK-
		CPP-1.DS04.task_ID = prior CPP_status_date	
type	х	Task type selection: • TD = task dependent. Task is scheduled using its task calendar. • RD = resource dependent. Task is scheduled using its resource calendar(s). • LOE = level of effort. Task duration by its dependent taks. Used for administration type tasks. Use should be limited. Likely DS04.EVT = A (level of effort) but could be different. Should have a start-to-start and a finish-to-finish predecessor relationship to a discrete tasks(s). • SM = start milestone. Tasks with 0 duration and no resources. • FM = finish milestone. Task with 0 duration and no resources. • WS = WBS summary. Task of aggregated tasks with common DS04.WBS_ID. Use should be limited.	string, select from: TD, RD, LOE, SM FM, WS
		DS04.type	
		CPP-1.DS04.type = prior CPP_status_date	
description	Х	Unique task description. Should be descriptive with a verb.	string, maxLength: 255
		DS04.description	
subtype		Task subtype selection: • SVT = A non-PMB task for visibility/functionality to charactarize potential impacts to the logic-driven network. Generally based on another project as a predecessor with a finish-to-start relationship. Generally constrained based on programmatic schedule with DS04.constraint_type = CS.MSOA or DS04.constraint_type = CS.MEOA but may be a hard constraint; DS04.constraint_type = M; not resource loaded. • ZBA = zero budget activity. For subK payment tasks. Used on a limited basis; not resource loaded. Align with DS04.milestone_level = 8xx.	string, select from: SVT, ZBA
		DS04.subtype	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
milestone_level		Milestone level selection for tasks that identify key milestones, deliverables, and control point dates (DSO4-type = SM or FM). Milestone level should align with DSO4-constraint_type as appropriate. • 1xx = DOE O 413.3B milestones. All 1xx are considered DSO4.task_subtype = SVT, unless otherwise noted. Required milestones: All DDE Order 413.3B milestones and milestones 100, 175, 180, 190, 195, 199. • 100 = approve borous tart project • 110 = approve CD-00-01 • 111 = approve CD-0R-02 • 120 = approve CD-10R-01 • 121 = approve CD-1R-01 • 122 = approve CD-1R-01 • 122 = approve CD-1R-02 • 130 = approve BCP-01 • 133 = approve BCP-01 • 133 = approve BCP-03 • 134 = approve BCP-03 • 138 = approve BCP-03 • 138 = approve BCP-03 • 139 = approve CD-3B • 140 = approve CD-3B • 141 = approve CD-3B • 142 = approve CD-3B • 142 = approve CD-3B • 144 = approve CD-3B • 144 = approve CD-3F • 150 = approve CD-3F • 150 = approve CD-4B • 160 = approve CD-4B • 161 = approve CD-4B • 162 = approve CD-4E • 165 = approve CD-4E • 165 = approve CD-4F • 175 = End of PMB. Planned/estimated completion with UB (calculated schedule reserve should align with duration from DS04 milestone_level = 175 to DS04.milestone_level = 180; should be aligned with DS03 last BCWS for BL or last ETC for FC to achieve CD-4; this is the end of the PARS ID; not SVT) • 190 = approve CD-44 • 195 = approve CD-45 • 193 = approve CD-46 • 195 = approve CD-47 • 190 = approve CD-48 • 195 = approve CD-48 • 196 = approve CD-48 • 197 = bend of PMB. Planned/estimated completion with UB (calculated schedule reserve should align with duration from DS04.milestone_level = 175 to DS04.milestone_level = 180 to DS04.milestone_level = 190) (Should be aligned with CBB date for BL or est CBB date for FC) (not SVT) • 190 = approve CD-4 • 195 = approve cD-4 • 195 = approve coeout • 199 = approve milestones. All 3xx are considered DS04.task_subtype = SVT. • 4xx = programmatic driven milestones • 5xx = major internal driven milestones • 6xx = minor internal driven milestones; align with DS	integer, min. value: 100, max. value: 999 100, 110, 195
milestone_level_descri ption		Milestone level description. Should align with DS04.milestone_level. Should be descriptive with a verb.	string, maxLength: 50
WBS_ID	X	DS04.milestone_level_description WP or PP or SLPP WBS identifier. Explain in DS04.justification_WBS if DS01.type	string, maxLength: 50
		is not WP, PP or SLPP. DS04.WBS_ID	
justification_WBS		Justification narrative for WBS identifier is not WP or PP or SLPP WBS. Not required if no justification narrative for WBS identifier is not WP or PP or SLPP WBS. DS04 justification WBS	string
CAM		DS04.justification_WBS CAM selection:	string, maxLength: 100
CAIN		CAM name for DS01.type = CA, WP, PP. Project manager name for DS01.type = SLPP. Project or appropriate manager name for DS01.type = WBS Format: [last name] space [first name] space [middle initial, optional]. Should align with DS01.CAM.	Whitney Zachary B, Burks Deanna A, Simon Avaya S, Moses Kendall
		DS04.CAM	



field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
		angue nou donaire (primary a dalediated)	охатрю
EVT		EVT selection that should be aligned with DS03.EVT (explanations should go in DS04.justification_EVT): • A = LOE. Should have a start-to-start and a finish-to-finish predecessor relationship to a discrete task(s). • B = weighted milestones (explain if utilized) • C = percent complete or for use in DS03, discrete (combination of discrete DS03.EVT excluding A, J, K, M, or NA) • D = units complete • E = 50-50 • F = 0-100	string, select from: A, B, C, D, E, F, G, J, K, L, M, N, O, P
		 G = 100-0 (explain if utilized) H = variation of 50-50 (explain if utilized) J = apportioned (explain if utilized). Should have a start-to-start and a finish-to-finish predecessor relationship to a discrete task(s). K = planning package (overrides where DS01.type = PP or SLPP) L = assignment percent complete (explain if utilized) M = calculated apportionment (explain if utilized). Should have a start-to-start and a finish-to-finish predecessor relationship to a discrete task(s). N = steps (explain if utilized) O = earned as spent (explain if utilized) P = percent manual entry (explain if utilized) Discrete EVTs for metrics consists of B, C, D, E, F, G, H, L, N, O, P. 	
justification_EVT		Justification narrative where DS04.EVT = B, G, H, J, L, M, N, O, or P.	string
EVT I to took ID		DS04.justification_EVT	atria a
EVT_J_to_task_ID		task_ID apportioned to, if DS04.EVT = J. DS04.EVT_J_to_task_ID	string
EVT_J_pct		Percent apportioned, if apportioned from another DS04.task ID.	number, max. of 2 decimal places
<u>-</u>		DS04.EVT_J_pct	
ES_date	Х	Early start date.	string, must be date as YYYY-MM-DD
		DS04.ES_date	2020-01-01, 2019-02-026, 2020-10-14
		DS04.ES_date_DS03 = aligned to DS03 period date	
EF_date	X	Early finish date.	string, must be date as YYYY-MM-DD
		DS04.EF_date	2020-01-01, 2019-02-026, 2020-10-14
		DS04.EF_date_DS03 = aligned to DS03 period date	
LS_date	X	Late start date.	string, must be date as YYYY-MM-DD
		DS04.LS_date	2020-01-01, 2019-02-026, 2020-10-14
LF_date	Х	Late finish date.	string, must be date as YYYY-MM-DD
		DS04.LF_date	2020-01-01, 2019-02-026, 2020-10-14
AS_date		Actual start date.	string, must be date as YYYY-MM-DD
		DS04.AS_date	2020-01-01, 2019-02-026, 2020-10-14
		CPP-1.DS04.AS_date = prior CPP_status_date	
AF_date		Actual finish date.	string, must be date as YYYY-MM-DD
		DS04.AF_date	2020-01-01, 2019-02-026, 2020-10-14
		CPP-1.DS04.AF_date = prior CPP_status_date	
duration_original_days	X	Original duration (work days).	number, max. of 2 decimal places
_ •		DS04.duration_original_days	,
duration_remaining_da	X	Remaining duration (work days).	number
ys		DS04.duration_remaining_days	
duration_actual_days	Х	Actual duration (work days).	number, max. of 2 decimal places
		DS04.duration_actual_days	
float_free_days	Х	Free float (work days).	number, max. of 2 decimal places
		DS04.float_free_days	
float_total_days	Х	Total float (work days).	number, max. of 2 decimal places
		DS04.float_total_days	
justification_float_high		Justification narrative for high float, DS04.float_total_days.	string
		DS04.justification_float_high	



			To the state of th
field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
haddlandan Inn		halffuria according to be added as with a with a section of the se	atria n
justification_lag		Justification narrative for lag relation with predecessor, DS05.lag_days <> 0.	string
driving_path	X	DS04.justification_lag Task is on the longest path or on the driving path (Y or N).	string, select from: Y, N
unving_path	^	DS04.driving_path	Stillig, Select Hom. 1, 14
RMT_ID		Align with only one DS15.risk_ID.	string, maxLength: 50
KWI _ID		Provide if an RMT.	String, maxcengur. 30
		DS04.RMT_ID	
PC_type	Х	% complete type selection (% complete used to calculate BCWP): • duration (utilized when DS04.type = LOE or DS04.EVT = A) • physical (utilized when DS04.type <> LOE, and DS04.EVT <> A) • units (utilized when DS06.EOC = material)	string, select from: duration, physical units
		DS04.PC_type	
PC_duration	Х	Duration % complete. If % complete = 100% , 1.00 . If 99% <= % complete < 100% , 0.99 (truncate remainder). If $0 < \%$ complete < 99% , round to 2 digits. If $0 = \%$ complete, 0.00 .	number, max. of 2 decimal places, m value: 0, max. value: 1
		DS04.PC_duration	
PC_physical	X	Physical % complete. If % complete = 100%, 1.00. If 99% <= % complete < 100%, 0.99 (truncate remainder). If 0 < % complete < 99%, round to 2 digits. If 0 = % complete, 0.00. Utilize if DS04.type = TD or RD.	number, max. of 2 decimal places, m value: 0, max. value: 1
DO 11		DS04.PC_physical	
PC_units	Х	Units % complete. If % complete = 100%, 1.00. If 99% <= % complete < 100%, 0.99 (truncate remainder). If 0 < % complete < 99%, round to 2 digits. If 0 = % complete, 0.00. Utilize if DS04.type = TD or RD and DS06.EOC = material.	number, max. of 2 decimal places, m value: 0, max. value: 1
		DS04.PC_units	
constraint_type		Start primary constraint type selection: CS_ASAP = as soon as possible (not considered a soft or hard constraint) CS_MSOB = must start on (considered hard constraint) CS_MSOB = must start on (considered hard constraint) CS_MSOB = must start on or after (considered soft constraint) CS_MSOB = must start on or before (considered hard constraint) Finish primary constraint type selection: CS_ALAP = as late as possible (not considered a soft or hard constraint) CS_MANDFIN = mandatory finish (considered hard constraint) CS_MEOB = must finish on (considered hard constraint) CS_MEOB = must finish on or after (considered hard constraint) CS_MEOB = must finish on or before (considered hard constraint) Provide hard constraint justification in DS04.justification_constraint_soft. Identify secondary constraint in DS04.justification_constraint_soft.	string, select from: CS_ASAP, CS_MANDSTART, CS_MSO, CS_MSOA, CS_MSOB, CS_ALAP, CS_MANDFIN, CS_MEO, CS_MEO, CS_MEOB
constraint_date		Primary constraint date.	string, must be date as YYYY-MM-DE
		Not required if DS04.constraint_type = CS_ALAP or not provided.	2020-01-01, 2019-02-026, 2020-10-1
luctification constrain		DS04.constraint_date	otring
justification_constrain t_hard		Justification narrative for hard constraint, DS04.constraint_type. DS04.justification_constraint_hard	string
justification_constraint		Justification narrative for soft constraint, DS04.constraint_type.	string
_soft		DS04.justification_constraint_soft	string
iustification constrain			atrina
justification_constrain t_secondary		Description and justification narrative for secondary start and finish constraints. DS04.justification constraint secondary	string
HDV_CI_ID		HDV-CI identifier. The data should align with DS14.HDV_CI_ID.	string, maxLength: 50
		DS04.HDV_CI_ID	
RPG	Х	Task is for a reprogramming effort. DS04.RPG	string, select from: Y, N
calendar_name		Calendar name for task. Align with DS19.calendar_name and DS20.calendar_name. Required unless task is an SVT.	string, maxLength: 50



field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
subproject ID		Unique subproject identifier. Tasks not in project scope should be associated with that task's primary project, not this project's primary project. This includes SVTs, tasks pre-CD-0, and tasks post DS04.milestone_level = 175.	string, maxLength: 100
		DS04.subproject_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
S05 schedule_logic			
lescription		This data set should be populated with the project's contractor BL and FC IMS tool task relationship data for the DS04 tasks. The contractor BL and FC IMS tool task relationship data by task and predecessor. There should be alignment between the BL and FC IMSs.	
schedule type	Х	Schedule type selection: • BL = baseline • FC = forecast The data should be scheduled by the schedule tool. DS05.schedule_type	string, select from: BL, FC
ask ID	Х	Unique task identifier.	string, maxLength: 50
predecessor task ID	Х	DS05.task_ID Task identifier of the predecessor task. The data should align with DS04.task_ID.	string, maxLength: 50
		DS05.predecessor_task_ID	
type	Х	Task relationship (task to its predecessor) selection: FS = finish to start SS = start to start FF = finish to finish	string, select from: FS, SS, SF, FF
		DS05.type	
ag_days	Х	Task relationship lag (work days) based on predecessor's calendar. The data is positive if lag. The data is negative if lead.	number, max. of 2 decimal places
		DS05.lag_days	
subproject ID		Unique subproject identifier.	string, maxLength: 100
		DS05.subproject_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS06 schedule_resources			
description		This data set should be populated with the project's contractor BL and FC IMS tool task role and resource data for the DS04 tasks. Provide the contractor BL and FC IMS tool task role and/or resource data by task. There should be alignment between the BL and FC IMSs.	
schedule type	Х	Schedule type selection: • BL = baseline • FC = forecast The data should be scheduled by the schedule tool. DS06.schedule_type	string, select from: BL, FC
task ID	Х	Unique task identifier. DS06.task_ID	string, maxLength: 50
resource ID		Unique resource identifier. DS06.resource_ID	string, maxLength: 50
resource name		Unique resource name. DS06.resource_name	string, maxLength: 100
role ID		Unique role identifier. DS06.role_ID	string, maxLength: 50
role name		Unique role name. DS06.role_name	string, maxLength: 100
type	X	Resource type selection: • labor where DS06.EOC = labor • nonlabor where DS06.EOC is not labor • material where DS06.EOC is not labor DS06.type	string, select from: labor, nonlabor, material
EOC	Х	EOC selection: • labor • material • subcontract • ODC • indirect (may be used after coordination with PM. To consist only of indirect costs) DS06.EOC	string, select from: labor, material, subcontract, ODC, indirect
start_date	Х	Resource start date. For FC IMS, updated resource start or started date.	string, must be date as YYYY-MM-DD 2020-01-01, 2019-02-026, 2020-10-14
finish_date	Х	Resource finish date. For FC IMS, updated resource finish or finished date.	string, must be date as YYYY-MM-DD 2020-01-01, 2019-02-026, 2020-10-14
oudget_dollars	Х	DS06.finish_date Total budget (dollars) aligned with BCWS. DS06.budget_dollars	number
actual_dollars	Х	Total actual (dollars) aligned with BCWP. DS06.actual_dollars	number, max. of 2 decimal places
remaining_dollars	Х	Total remaining (dollars) aligned with ETC. DS06.remaining_dollars	number, max. of 2 decimal places
oudget_units	Х	Total budget (units) aligned with BCWS. Units of measure are specified in UOM field.	number, max. of 2 decimal places
octual_units	X	Total actual (units) aligned with BCWP. Units of measure are specified in UOM field. Note: This represents BCWP, not ACWP. DS06.actual_units	number, max. of 2 decimal places
remaining_units	Х	Total remaining (units) aligned with ETC. Units of measure are specified in UOM field.	number, max. of 2 decimal places
JOM	Х	Unit of measure. If resource_type is labor or non-labor, it is h. If it is material it is a string.	string, maxLength: 20 h, CY, LF, tons



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
lag_remaining_days	Х	Task relationship remaining lag (work days) based on predecessor's calendar. The data is positive if lag. The data is negative if lead.	number, max. of 2 decimal places
		DS06.lag_remaining_days	
lag_planned_days	Х	Task relationship planned lag (work days) based on predecessor's calendar. The data is positive if lag. The data is negative if lead.	number, max. of 2 decimal places
		DS06.lag_planned_days	
subproject ID		Unique subproject identifier.	string, maxLength: 50
		DS06.subproject_ID	
calendar_name	Х	Calendar name for resource. Align with DS19.calendar_name and DS20.calender_name.	string, maxLength: 50
		DS06.calendar_name	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-02-24, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example: string, integer
DS07 IPMR_header			
description		This object should be populated with the project's contractor IPMR header data aligned with DS01 to DS06 and DS09 to DS12. Provide the contractor EVMS cost tool IPMR header data. This object contains IPMR header information so does not have an array of objects like other DS objects.	
K_ID	Х	Unique DOE contract number and, if applicable, CLIN(s). DS07.K_ID	string, maxLength: 255
type		Contract type selection: FFP = firm fixed price FPE = fixed price escalation FPI = fixed price incentive CPIF = cost plus incentive fee CPAF = cost plus sward fee CPDS = cost plus fixed fee CPE = cost plus price fixed fee CPE = cost plus percentage DS07.type	string, select from: FFP, FPE, FPI, CPIF CPAF, CPDS, CPE, CPP
UB_bgt_days	Х	UB, budget applicable to the contract effort not yet distributed to the WBS identifiers at or below the reporting level (work days). DS07.UB_bgt_days	number, max. of 2 decimal places
UB_est_days	Х	EAC for scope of work represented by the UB (work days). DS07.UB_est_days	number, max. of 2 decimal places
UB_bgt_dollars	Х	UB, budget applicable to the contract effort not yet distributed to the WBS identifiers at or below the reporting level. DS07.UB_bgt_dollars	number, max. of 2 decimal places
UB_est_dollars	Х	EAC for scope of work represented by the UB. DS07.UB_est_dollars	number, max. of 2 decimal places
MR_bgt_dollars	Х	MR excluding OTB and OTS. DS07.MR_bgt_dollars	number, max. of 2 decimal places
MR_rpg_dollars	Х	MR reprogramming adjustment factoring OTB and OTS. DS07.MR_rpg_dollars	number, max. of 2 decimal places
AUW_dollars	Х	AUW of the authorized, unpriced work for approved work scope that has not been definitized by the contracting officer. Amount is the procuring contracting officer's best estimate. Excludes fee and profit. AUW cannot be negative. For effort descoped and not yet reflected in the CBB. DS07.AUW_dollars	number, max. of 2 decimal places, min. value: 0
NCC_dollars	Х	NCC on which project was reached as of the reflected reporting period. Excludes fee and profit. For an incentive contract, the definitized contract target cost. For a cost plus fixed fee or award fee contract, the estimated negotiated cost that consists only of the estimates amount for changes in the contract scope of work and not for cost change (overrun or underrun) from the original cost. Amount for changes shall not be included until definitized in the contract.	number, max. of 2 decimal places
		DS07.NCC_dollars	
CBB_dollars	Х	CBB, the NCC plus AUW. DS07.CBB_dollars	number, max. of 2 decimal places
OTB_OTS_date		Date last OTB or OTS was approved by DOE and implemented. Not required if no OTB or OTS.	string, must be date as YYYY-MM-DD 2020-01-01,2019-02-026,2020-10-14



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example: string, integer
TAB_dollars	Х	TAB, total budget value allocated to the performance of the contractual effort including MR and UB. Excludes fee and profit.	number, max. of 2 decimal places
		DS07.TAB_dollars	
rofit_fee_dollars		Target profit or fee that applies to the negotiated contract cost.	number, max. of 2 decimal places
		DS07.profit_fee_dollars	
EAC_PM_best_dollars		Contractor's best case EAC for the contract cost for all authorized contractual efforts. Excludes fee and profit.	number, max. of 2 decimal places
		DS07.EAC_PM_best_dollars	
EAC_PM_likely_dollars	Х	Contractor's most likely case EAC for the contract cost for all authorized contractual efforts. Excludes fee and profit.	number, max. of 2 decimal places
		DS07.EAC_PM_likely_dollars	
EAC_PM_worst_dollars		Contractor's worst case EAC for the contract cost for all authorized contractual efforts. Excludes fee and profit.	number, max. of 2 decimal places
		DS07.EAC_PM_worst_dollars	
EAC_PM_best_date	Х	Contractor's best case EAC date for all authorized contractual efforts.	string, must be date as YYYY-MM-DD
		DS07.EAC_PM_best_date	
AC_PM_likely_date	Х	Contractor's most likely case EAC date for all authorized contractual efforts.	string, must be date as YYYY-MM-DD
		DS07.EAC_PM_likely_date	
EAC_PM_worst_date	Х	Contractor's worst case EAC date for all authorized contractual efforts.	string, must be date as YYYY-MM-DE
		DS07.EAC_PM_worst_date	
escalation_rate_pct	Х	Escalation rate for DS07.TAB.	number, max. of 2 decimal places
		DS07.escalation_rate_pct	
QRA_CL_cost_pct	Х	Quantitative risk analysis confidence level for cost DS07.MR_rpg and DS07.MR_bgt.	number, max. of 2 decimal places, mi value: 0, max. value: 1
		DS07.QRA_CL_cost_pct	
QRA_CL_schedule_pct	Х	Quantitative risk analysis confidence level for schedule and aligned with DS07.MR_rpg and DS07.MR_bgt.	number, max. of 2 decimal places, mi value: 0, max. value: 1
		DS07.QRA_CL_schedule_pct	
hreshold_cost_cum_doll	X	Project cost threshold (dollar) for cumulative variance analysis at CA WBS level,	number, max. of 2 decimal places
ır_fav		favorable. DS07.threshold_cost_cum_dollar_fav	
hh-ldt d-ll			and the second of the first of the second
hreshold_cost_cum_doll r_unfav	Х	Project cost threshold (dollar) for cumulative variance analysis at CA WBS level, unfavorable.	number, max. of 2 decimal places
		DS07.threshold_cost_cum_dollar_unfav	
hreshold_cost_cum_pct fav	Х	Project cost threshold (percent) for cumulative variance analysis CA WBS level, favorable.	number, max. of 2 decimal places, mi value: 0, max. value: 1
		DS07.threshold_cost_cum_pct_fav	
hreshold_cost_cum_pct unfav	Х	Project cost threshold (percent) for cumulative variance analysis CA WBS level, unfavorable.	number, max. of 2 decimal places, mi
_unrav		DS07.threshold_cost_cum_pct_unfav	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example: string, integer
threshold_cost_inc_dolla r_fav	Х	Project cost threshold (dollar) for incremental variance analysis CA WBS level, favorable.	number, max. of 2 decimal places
		DS07.threshold_cost_inc_dollar_fav	
hreshold_cost_inc_dolla _unfav	Х	Project cost threshold (dollar) for incremental variance analysis CA WBS level, unfavorable.	number, max. of 2 decimal places
		DS07.threshold_cost_inc_dollar_unfav	
hreshold_cost_inc_pct_ av	Х	Project cost threshold (percent) for incremental variance analysis CA WBS level, favorable.	number, max. of 2 decimal places, min value: 0, max. value: 1
		DS07.threshold_cost_inc_pct_fav	
hreshold_cost_inc_pct_ infav	Х	Project cost threshold (percent) for incremental variance analysis CA WBS level, unfavorable.	number, max. of 2 decimal places, min value: 0, max. value: 1
		DS07.threshold_cost_inc_pct_unfav	
hreshold_cost_VAC_doll ar_fav	Х	Project cost threshold (dollar) for VAC at project level, favorable.	number, max. of 2 decimal places
		DS07.threshold_cost_VAC_dollar_fav	
hreshold_cost_VAC_doll ar_unfav	Х	Project cost threshold (dollar) for VAC at project level, unfavorable.	number, max. of 2 decimal places
		DS07.threshold_cost_VAC_dollar_unfav	
hreshold_cost_VAC_pct fav	Х	Project cost threshold (percent) for VAC at project level, favorable.	number, max. of 2 decimal places, mir value: 0, max. value: 1
_iav		DS07.threshold_cost_VAC_pct_fav	value. 0, max. value. 1
threshold_cost_VAC_pct _unfav	Х	Project cost threshold (percent) for VAC at project level, unfavorable.	number, max. of 2 decimal places, min value: 0, max. value: 1
		DS07.threshold_cost_VAC_pct_unfav	
threshold_schedule_cum_ dollar_fav	Х	Project schedule threshold (dollar) for cumulative variance analysis at CA WBS level, favorable.	number, max. of 2 decimal places
		DS07.threshold_schedule_cum_dollar_fav	
threshold_schedule_cum _dollar_unfav	Х	Project schedule threshold (dollar) for cumulative variance analysis at CA WBS level, unfavorable.	number, max. of 2 decimal places
		DS07.threshold_schedule_cum_dollar_unfav	
hreshold_schedule_cum _pct_fav	Х	Project schedule threshold (percent) for cumulative variance analysis CA WBS level, favorable.	number, max. of 2 decimal places, min value: 0, max. value: 1
		DS07.threshold_schedule_cum_pct_fav	
hreshold_schedule_cum _pct_unfav	Х	Project schedule threshold (percent) for cumulative variance analysis CA WBS level. unfavorable.	number, max. of 2 decimal places, min value: 0, max. value: 1
		DS07.threshold_schedule_cum_pct_unfav	
hreshold_schedule_inc_d bllar fav	Х	Project schedule threshold (dollar) for incremental variance analysis CA WBS level, favorable.	number, max. of 2 decimal places
UIIAI_IAV		DS07.threshold_schedule_inc_dollar_fav	
hreshold_schedule_inc_ dollar_unfav	Х	Project schedule threshold (dollar) for incremental variance analysis CA WBS level, unfavorable.	number, max. of 2 decimal places
		DS07.threshold_schedule_inc_dollar_unfav	
hreshold_schedule_inc_ oct_fav	Х	Project schedule threshold (percent) for incremental variance analysis CA WBS level, favorable.	number, max. of 2 decimal places, mir value: 0, max. value: 1
pct_fav		DS07.threshold_schedule_inc_pct_fav	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example: string, integer
threshold_schedule_inc_ pct_unfav	Х	Project schedule threshold (percent) for incremental variance analysis CA WBS level, unfavorable.	number, max. of 2 decimal places, min. value: 0, max. value: 1
		DS07.threshold_schedule_inc_pct_unfav	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS08 WAD			
description		This data set should be populated with the approved project's contractor WAD data	
		for the entire span of the project (not the contract) to include from initial and all revisions.	
		The contractor WAD data by CA and SLPP WBS level and optional by PP and WP WBS levels.	
WAD ID	Х	Unique WAD identifier.	string, maxLength: 50
		DS08.WAD_ID	
revision		WAD version.	string, maxLength: 50
		DS08.revision	
title	Х	WAD title.	string, maxLength: 255
		DS08.title	
WBS ID	Х	CA or SLPP WBS identifier.	string, maxLength: 50
		DS08.WBS_ID	
WBS ID WP		WP or PP WBS identifier.	string
		DS08.WBS_ID_WP	
auth_PM_date		Date WAD was last signed by contractor project manager.	string, maxLength: 255
		DS08.auth_PM_date	
auth_CAM_date		Date WAD was last signed by CAM.	string, maxLength: 255
		DS08.auth_CAM_date	
auth_WPM_date		Date WAD was last signed by WPM.	string, maxLength: 255
		DS08.auth_WPM_date	
initial_auth_date		Date WAD was inititally signed by contractor project manager.	string, must be date as YYYY-MM-DD
		DS08.initial_auth_date	2020-01-01, 2019-02-026, 2020-10-14
EVI		Provide if WBS_ID_WP is provided. EVT selection that should be aligned with DS03.EVT and DS04.EVT: • A = LOE • B = weighted milestones • C = percent complete or for use in DS03, discrete • D = units complete • E = 50-50 • F = 0-100 • G = 100-0 • H = variation of 50-50 • J = apportioned • K = planning package (overrides where DS01.type = PP or SLPP) • L = assignment percent complete • M = calculated apportionment • N = steps • O = earned as spent • P = percent manual entry Discrete EVTs for metrics consists of B, C, D, E, F, G, H, L, N, O, P.	string, select from: A, B, C, D, E, F, G, F J, K, L, M, N, O, P, NA
budget_labor_dollars	X	Total budget for EOC labor (dollars). DS08.budget_labor_dollars	number, max. of 2 decimal places
budget_material_dollar	Х	Total budget for EOC material (dollars).	number, max. of 2 decimal places
s		DS08.budget_material_dollars	
budget_subcontract_do llars		Total budget for EOC subcontract (dollars).	number, max. of 2 decimal places
liars		DS08.budget_subcontract_dollars	
budget_ODC_dollars	Х	Total budget for EOC ODC (dollars).	number, max. of 2 decimal places
		DS08.budget_ODC_dollars	
budget_indirect_dollars	Х	Total budget for EOC indirect (dollars).	number, max. of 2 decimal places
		DS08.budget_indirect_dollars	
budget_labor_hours	Х	Total labor budget (hours).	number, max. of 2 decimal places
		DS08.budget_labor_hours	
POP_start_date	Х	WBS POP start date, as defined by the latest approved baseline change. Not required if DS10.transaction_ID is not DB.	string, must be date as YYYY-MM-DD 2020-01-01, 2019-02-026, 2020-10-14
		DS08.POP_start_date	
		DS08.POP_start_date [period] = aligned to DS03 period date	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
POP_finish_date	Х	WBS POP finish date, as defined by the latest approved baseline change. Not required if DS10.transaction ID is not DB.	string, must be date as YYYY-MM-DD
		_	2020-01-01, 2019-02-026, 2020-10-14
		DS08.POP_finish_date	
		DS08.POP_finish_date [period] = aligned to DS03 period date	
CAM	Х	CAM who signed WAD. Format: [last name] space [first name] space [middle initial, optional]	string, maxLength: 100
		DS08.CAM	
WPM		PP or WP WBS level manager. Optional if DS01.type = PP or WP. Format: [last name] space [first name] space [middle initial, optional]	string, maxLength: 100
		DS08.WPM	
PM	Х	Contractor project manager. Format: [last name] space [first name] space [middle initial, optional]	string, maxLength: 100
		DS08.PM	
narrative	Х	CA WBS scope statement (not title) encompassing all scope per WAD and aligned with DS01.narrative and DS02.narrative.	string
		DS08.narrative	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS09 CC_log			
description		This data set should be populated with the project's contractor project change control log data for the entire span of the project (not the contract). Provide the contractor approved project change control log data by CC_log identifer. The data should include the initial CC_log and the initial deposit at the start of the project.	
CC log ID	Х	CC identifier.	string, maxLength: 50
		DS09.CC_log_ID	
CC log ID supplement		Supplemental CC_log_ID, e.g. revisions.	string, maxLength: 50
		DS09.CC_log_ID_supplement	
CC_log_ID_original_UB		For CCs that are approving distribution of budget from UB, this should have original CC_log_ID that approved increase of UB account through AUW or modification.	string, maxLength: 50
type	Х	DS09.CC_log_ID_original_UB BCP type selection (per DOE EVMS glossary): • Funding • BCP • BCP • BCR	string, select from: BCP, BCR, Funding
		DS09.type	
K_mod_ID		Provide when CC_log_ID is associated with a contract mod.	string
		DS09.K_mod_ID	
description	Х	Scope description. (Do not include unapproved changes)	string
		DS09.description	
approved_date	Х	Approved date.	string, must be date as YYYY-MM-DD
		DS09.approved_date	2020-01-01, 2019-02-026, 2020-10-14
implementation_date	Х	Date during which the change has been implemented within contractor systems.	string, must be date as YYYY-MM-DD
		DS09.implementation_date	2020-01-01, 2019-02-026, 2020-10-14
dollars_delta		Total increase or decrease in CA WBS budgeted dollars authorized by the change request.	number, max. of 2 decimal places
		DS09.dollars_delta	
hours_delta		Total increase or decrease in CA WBS budgeted number of hours authorized by the change request.	number, max. of 2 decimal places
		DS09.hours_delta	
PM		Contractor project manager. Format: [last name] space [first name] space [middle initial, optional]	string, maxLength: 100
		DS09.PM	
risk_ID		List of risk_IDs addressed by CC_log_ID. Aligns with DS15.risk_ID. If multple identifiers, seperate with semicolons.	string, maxLength: 100
		DS09.risk_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v05.00, 2023-02-8, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS10 CC_log_detail			
description		This data set should be populated with the project's contractor project change control log transaction data for DS09. Provide the contractor approved project change control log transaction data by CC_log identifier. The data should consist of CC_logs, each resulting in zero-sum of dollars that are moved between the transaction categories, unless new budget is added to the CBB.	
transaction ID	Х	Unique transaction identifier.	string, maxLength: 50
		DS10.transaction_ID	
category	х	Transaction category selection: • CNT = DOE contingency • DB = distributed budget (should also be identified by the CA WBS) • UB = undistributed budget account • MR = management reserve account • OTB = over-target baseline only • OTS = over-target schedule only • OTB-OTS = OTB and OTS • funding • profit-fee	string, select from: CNT, DB, UB, MR, OTB, OTS, OTB-OTS, funding, profit-fe
		DS10.category	
CC log ID	Х	CC identifier.	string, maxLength: 50
		DS10.CC_log_ID	
description		Transaction summary information.	string
		DS10.description	
WBS_ID		WBS identifier. Project level required for UB, MR, CNT. CA or lower level required if transaction type is DB.	string, maxLength: 50
		DS10.WBS_ID	
dollars_delta		CC_log impact (dollars) that changes the balance.	number, max. of 2 decimal places, min. value: 0
		DS10.dollars_delta	
		CPP-1,2.DS10.dollars_delta = prior 1st,2nd CPP_status_date	
hours_delta		CC_log impact (hours) that changes the balance.	number, max. of 2 decimal places, min. value: 0
		DS10.hours_delta	
AUW	Х	Transaction is for AUW.	string, select from: Y, N
		DS10.AUW	
NTE_dollars_delta		NTE for DS10.AUW_dollars	number, max. of 2 decimal places
		DS10.NTE_dollars_delta	
POP_start_date		CA or WP WBS POP start date, only if modified.	string, must be date as YYYY-MM-DD
		DS10.POP_start_date	2020-01-01, 2019-02-026, 2020-10-14
POP_finish_date		CA or WP WBS POP finish date, only if modified.	string, must be date as YYYY-MM-DD
		DS10.POP_finish_date	2020-01-01, 2019-02-026, 2020-10-14
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS11 variance			
description		This data set should be populated with the project's contractor variance data. Provide the contractor variance data by WBS identifier; for project, use the project level WBS identifier.	
WBS ID	Х	WBS identifier.	string, maxLength: 50
		DS11.WBS_ID	
narrative type		Narrative type selection: 100 PRJ = project level summary 110 RPG = project level formal reprogramming analysis 120 VAC = project level VAC analysis 130 EAC = project level EAC analysis 140 UB = project level UB analysis 150 MR = project level MR analysis 160 IMS = project level IMS discussion 170 F3 = project level IPMR F3 discussion 180 F4 = project level IPMR F4 discussion 200 SLPP = summary level planning package (The data should not have SV or CV.) 300 CA = control account 400 PP = planning package (The data should not have SV or CV.)	string, select from: 100, 110, 120, 130, 140, 150, 160, 170, 200, 300, 400, 500
		• 500 WP = work package	
		DS11.narrative_type	
narrative_overall		Overall narrative. Provide if DS11.narrative_type <200	string
		DS11.narrative_overall	
narrative_RC_SVi		Root cause narrative for incremental schedule variance.	string
		DS11.narrative_RC_SVi	
narrative_RC_CVi		Root cause narrative for incremental cost variance.	string
porretive BC SVe		DS11.narrative_RC_CVi	atrina
narrative_RC_SVc		Root cause narrative for cumulative schedule variance. DS11.narrative_RC_SVc	string
narrative_RC_CVc		Root cause narrative for cumulative cost variance.	string
		DS11.narrative_RC_CVc	3
narrative_impact_techn		Impact narrative for technical variance.	string
ical		DS11.narrative_impact_technical	
narrative_impact_sche dule		Impact narrative for schedule variance.	string
		DS11.narrative_impact_schedule	
narrative_impact_cost		Impact narrative for cost variance.	string
		DS11.narrative_impact_cost	
CAL_ID		Unique corrective action log identifier(s). If multiple identifiers, separate with semicolons.	string
		DS11.CAL_ID	
approved_date		Approved date by CAM.	string, must be date as YYYY-MM-DD
		DS11.approved_date	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS12 variance_CAL			
description		This data set should be populated with the project's contractor corrective action data for DS11. Provide the contractor corrective action data by corrective action identifier. The data should validate that corrective actions for variances are addressed, monitored, and mitigated. The data may be limited to the corrective actions that are open or closed within the current reporting period, based on coordination with DOE.	
CAL ID	Х	Corrective action log identifier.	string
		DS12.CAL_ID	
transaction ID		Unique transaction identifier.	string, maxLength: 50
		DS12.transaction_ID	
narrative_schedule		Corrective action narrative for cumulative schedule variance.	string
		DS12.narrative_schedule	
narrative_cost		Corrective action narrative for cumulative cost variance.	string
		DS12.narrative_cost	
POC	Х	Name of the person responsible for closing corrective action. Does not have to be the same as CAM. Format: [last name] space [first name] space [middle initial, optional].	string, maxLength: 100
		DS12.POC	
status	Х	Current status of corrective action Item as it exists in contractor log. • open • closed	string, select from: open, closed
		DS12.status	
initial_date	Х	Date of the initial corrective action.	string, must be date as YYYY-MM-DD
		DS12.initial_date	2020-01-01, 2019-02-026, 2020-10-14
original_due_date	Х	Original due date by which corrective action was supposed to be closed.	string, must be date as YYYY-MM-DD
		DS12.original_due_date	2020-01-01, 2019-02-026, 2020-10-14
forecast_due_date	Х	Forecast due date that indicates expected closure date for the corrective action. DS12.closed_date if closed.	string, must be date as YYYY-MM-DD
		DS12.forecast due date	2020-01-01, 2019-02-026, 2020-10-14
closed_date		Actual date when corrective action was closed.	string, must be date as YYYY-MM-DD
		DS12.closed_date	2020-01-01, 2019-02-026, 2020-10-14
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.02, 2022-09-01, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v05.00, 2023-02-3, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS13 subK			
		This date get about the populated with the present a subsection trival, date as	
description		This data set should be populated with the project's subcontract work data as reported by the subcontractors to the contractor. The data should include all subcontracts that have discrete work and that have	
		schedule or cost reporting requirements. The data should be updated as subcontracts are negotiated.	
		schedule or cost reporting requirements. The data should be updated as subcontracts are negotiated. The data may be limited to a single line per subcontract due to type or size of the subcontract or data availability, based on coordination with DOE.	
subK_ID	Х	Unique subcontract identifier (e.g., subcontract name).	string, maxLength: 50
		DS13.subK_ID	
subK task ID	Χ	Unique task ID from subcontract schedule.	string, maxLength: 50
		DS13.subK_task_ID	
task ID	Χ	DS04.task_ID associated with subcontract work.	string, maxLength: 50
		DS13.task_ID	
BCWSc_dollars		BCWS cumulative (dollars).	number, max. of 2 decimal places
		DS13.BCWSc_dollars	
BCWPc_dollars		BCWP cumulative (dollars).	number, max. of 2 decimal places
		DS13.BCWPc_dollars	
ACWPc_dollars		ACWP cumulative (dollars).	number, max. of 2 decimal places
		DS13.ACWPc_dollars	
BAC_dollars		DB (dollars).	number, max. of 2 decimal places
		DS13.BAC_dollars	
BAC_initial_dollars		BAC initial (dollars).	number, max. of 2 decimal places
		DS13.BAC_initial_dollars	
EAC_dollars		EAC (dollars).	number, max. of 2 decimal places
		DS13.EAC_dollars	
BL_start_date		Baseline start date.	string, must be date as YYYY-MM-DD
		DS13.BL_start_date	2020-01-01, 2019-02-026, 2020-10-14
BL_finish_date		Baseline finish date.	string, must be date as YYYY-MM-DD
		DS13.BL_finish_date	2020-01-01, 2019-02-026, 2020-10-14
FC_start_date		Forecast start date.	string, must be date as YYYY-MM-DD
		DS13.FC_start_date	2020-01-01, 2019-02-026, 2020-10-14
FC_finish_date		Forecast finish date.	string, must be date as YYYY-MM-DD
		DS13.FC_finish_date	2020-01-01, 2019-02-026, 2020-10-14
AS_date		Actual start date.	string, must be date as YYYY-MM-DD
		DS13.AS_date	2020-01-01, 2019-02-026, 2020-10-14
AF_date		Actual finish date.	string, must be date as YYYY-MM-DD
		DS13.AF_date	2020-01-01, 2019-02-026, 2020-10-14
MR_dollars		MR Remaining (dollars).	number, max. of 2 decimal places
AND Indicate to the		DS13.MR_dollars	
MR_initial_dollars		MR initial (dollars).	number, max. of 2 decimal places
mundit for dellars		DS13.MR_initial_dollars	number may of 2 decimal places
profit_fee_dollars		Profit fee remaining (dollars). DS13.profit_fee_dollars	number, max. of 2 decimal places
profit foo oarnod dolla			number may of 2 decimal places
profit_fee_earned_dolla rs		Profit fee earned (dollars). DS13.profit_fee_earned_dollars	number, max. of 2 decimal places
profit_fee_initial_dollar		Profit fee initial (dollars).	number, max. of 2 decimal places
S		DS13.profit_fee_initial_dollars	
subK_PO_ID		Purchase order identifier.	string
0abit_i 0_ib		DS13.subK_PO_ID	Suring
		50.0.04DIT_I O_ID	
flow_down	X	DOE Order 413.3B CRD flow down required.	string, select from: Y, N



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS14 HDV_CI			
description		This data set should be populated with the project's contractor HDV-Cl data. Provide the contractor HDV-Cl data by WBS and HDV-Cl identifiers.	
HDV CI ID	Х	Unique HDV-CI identifier. This data should align with DS04.HDV_CI_ID.	string, maxLength: 50
		DS14.HDV_CI_ID	
description	Х	HDV-CI description.	string
		DS14.description	
subK_ID		Subcontract identifier.	string, maxLength: 50
		DS14.subK_ID	
subK_PO_ID		Purchase order identifier.	string, maxLength: 50
		DS14.subK_PO_ID	
equipment_ID		Equipment identifier.	string, maxLength: 50
		DS14.equipment_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.01, 2023-02-13, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description unique field identifier (primary & calculated)	JSON data type example
DS15 risk_register			
description		This data set should be populated with the project's contractor risk log for the entire span of the project (not the contract). Provide the contractor risk log by risk identifier. The data should be updated through the CPP_status_date.	
risk ID	Х	Unique risk identifier. DS15.risk_ID	string, maxLength: 50
revision		Current revision number for the DS15.risk_ID DS15.revision	string, maxLength: 50
description	Х	Risk description. Format: if then.	string, maxLength: 500
type	Х	DS15.description Risk type selection: • T = threat • O = opportunity	string, select from: T, O
manager	X	Risk manager. Format: [last name] space [first name] space [middle initial, optional]. DS15.manager	string, maxLength: 100
owner	Х	Risk owner selection: • federal • contractor	string, select from: federal, contractor
		DS15.owner	
approved_date		Approved date with risk handling selection.	string, must be date as YYYY-MM-Di 2020-01-01, 2019-02-026, 2020-10-
		DS15.approved_date	
realized_date		Date risk realized. DS15.realized_date	string, must be date as YYYY-MM-DI 2020-01-01, 2019-02-026, 2020-10-1
closed_date		Risk closed date when risk is no longer actively tracked but remains on the risk log.	string, must be date as YYYY-MM-DI
ologica_duto		DS15.closed_date	2020-01-01, 2019-02-026, 2020-10-
probability_schedule_m in_pct	Х	Risk event probability schedule min. (percent). DS15.probability_schedule_min_pct	number, max. of 2 decimal places, m value: 0, max. value: 1
probability_schedule_ max_pct	Х	Risk event probability schedule max. (percent). DS15.probability_schedule_max_pct	number, max. of 2 decimal places, m value: 0, max. value: 1
probability_cost_min_p ct	X	Risk event probability cost min. (percent). DS15.probability_cost_min_pct	number, max. of 2 decimal places, m value: 0, max. value: 1
probability_cost_max_p ct	Х	Risk event probability cost max. (percent). DS15.probability_cost_max_pct	number, max. of 2 decimal places, m value: 0, max. value: 1
risk_handling	Х	Risk handling selections: • avoid • mitigate • transfer • accept DS15.risk_handling	string, select from: avoid, mitigate, transfer, accept
basis		Notes. DS15.basis	string
revision		V01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-01, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
S16 risk_register_tasks			
escription		This data set should be populated with the project's contractor risk log tasks for the entire span of the project (not the contract). Provide the contractor risk log tasks by risk identifier. The data should be updated through the CPP_status_date.	
sk ID	Х	Risk identifier. Align with DS15.risk_ID.	string, maxLength: 50
		DS16.risk_ID	
isk task type	Х	Risk task type selections: • event (risk trigger, when risk is relevant. If no event task for a risk_ID, then assume risk is relevant for the entire project.) • impact	string, maxLength: 50
		DS16.risk_task_type	
ask ID	Х	Event or impact task identifer. Aligned with DS04.task_ID and based on DS16.risk_task_type.	string, maxLength: 50
		DS16.task_ID	
mpact_schedule_min_ ays		Provide if DS16.risk_task_type = impact, schedule impact (calendar days) min.	number, max. of 2 decimal place
ays		DS16.impact_schedule_min_days	
mpact_schedule_likel _days		Provide if DS16.risk_task_type = impact, schedule impact (calendar days) most likely.	number, max. of 2 decimal place
		DS16.impact_schedule_likely_days	
mpact_schedule_max_ lays		Provide if DS16.risk_task_type = impact, schedule impact (calendar days) max.	number, max. of 2 decimal place
lays		DS16.impact_schedule_max_days	
mpact_cost_min_dolla s		Provide if DS16.risk_task_type = impact, cost impact (dollars) min.	number, max. of 2 decimal places
5		DS16.impact_cost_min_dollars	
mpact_cost_likely_doll		Provide if DS16.risk_task_type = impact, cost impact (dollars) most likely.	number, max. of 2 decimal place
rs		DS16.impact_cost_likely_dollars	
mpact_cost_max_dolla		Provide if DS16.risk_task_type = impact, cost impact (dollars) max.	number, max. of 2 decimal places
s		DS16.impact_cost_max_dollars	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
S17 WBS_EU			
description		This data set should be populated with the project's contractor WBS EU data for each DS01.WBS and basis documented. Provide the contractor WBS EU data.	
WBS ID	Х	Unique contractor WP or PP WBS identifier.	string, maxLength: 50
		DS17.WBS_ID	
EOC	х	EOC selection: • labor • material • subcontract • ODC	string, select from: labor, material, subcontract, ODC
		DS17.EOC	
EU_min_dollars	Х	EU min. (dollars) work remaining.	number, max. of 2 decimal places
		DS17.EU_min_dollars	
EU_likely_dollars	Х	EU most likely (dollars) work remaining.	number, max. of 2 decimal places
		DS17.EU_likely_dollars	
EU_max_dollars	Х	EU max. (dollars) work remaining.	number, max. of 2 decimal places
		DS17.EU_max_dollars	
time_dependent	Х	WBS is time-dependent (Y or N) for one or more associated tasks.	string, select from: Y, N
		DS17.time_dependent	
justification_EU		Basis. Add justification narrative if WBS EU distribution is not triangular. Not required if WBS EU distribution is triangular or WBS is completed or closed.	string
		DS17.justification_EU	
subproject ID		Unique subproject identifier.	string, maxLength: 50
		DS17.subproject_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-3, PM-30, Melvin Frank, Updated for release. v05.00, 2023-02-8, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
S18 schedule_EU			
escription		This data set should be populated with the project's contractor task EU data for each DS04.task_ID. Provide the contractor schedule EU data.	
schedule type	Х	Schedule type selection: • BL = baseline • FC = forecast	string, select from: BL, FC
		DS18.schedule_type	
ask ID	Х	Unique task identifier.	string, maxLength: 50
		DS18.task_ID	
EU_min_days	Х	EU min. (work days) remaining.	integer
		DS18.EU_min_days	
EU_likely_days	Х	EU most likely (work days) work remaining.	integer
		DS18.EU_likely_days	
EU_max_days	Х	EU max. (work days) work remaining.	integer
		DS18.EU_max_days	
justification_EU		Basis. Add justification narrative if activity is incomplete and task EU distribution is not triangular.	string
		DS18.justification_EU	
subproject ID		Unique subproject identifier.	string, maxLength: 50
		DS18.subproject_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-29, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-14, PM-30, Melvin Frank, Updated for release.	



			10011 1 4 4
field name	req'd	description unique field identifier (primary & calculated)	JSON data type
		unique neid identiner (primary & carculated)	example
DS19 schedule_calendar_std			
description		This data set should be populated with the project's contractor IMS tool standard work week calendar data for the entire span of the project (not the contract). Each weekday is limited to 3 shifts (A, B, and C) for breaks in between shifts, starting with shift A, half hour increments, and no overlaps. If more than 3 shifts, 3rd shift should be stretched to the last shift. There should be alignment between the BL and FC IMSs.	
calendar name	Х	Unique calendar name.	string, maxLength: 50
		DS19.calendar_name	
hours_per_day	Χ	Hours per day.	number, max. of 2 decimal places
		DS19.hours_per_day	
std_01_Mon_shift_A_st art time		Standard work week shift_A_start time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_01_Mon_shift_A_start_time	
std_01_Mon_shift_A_st op_time		Standard work week shift_A_stop time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
- F =		DS19.std_01_Mon_shift_A_stop_time	
std_01_Mon_shift_B_st art time		Standard work week shift_B_start time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_01_Mon_shift_B_start_time	
std_01_Mon_shift_B_st op_time		Standard work week shift_B_stop time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_01_Mon_shift_B_stop_time	<u> </u>
std_01_Mon_shift_C_st art_time		Standard work week shift_C_start time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_01_Mon_shift_C_start_time	<u> </u>
std_01_Mon_shift_C_st op_time		Standard work week shift_C_stop time, Monday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_01_Mon_shift_C_stop_time	
std_02_Tue_shift_A_sta rt_time		Standard work week shift_A_start time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_A_start_time	
std_02_Tue_shift_A_st op_time		Standard work week shift_A_stop time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_A_stop_time	<u> </u>
std_02_Tue_shift_B_sta rt_time		Standard work week shift_B_start time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_B_start_time	<u> </u>
std_02_Tue_shift_B_st op_time		Standard work week shift_B_stop time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_B_stop_time	<u> </u>
std_02_Tue_shift_C_sta rt_time		Standard work week shift_C_start time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_C_start_time	<u> </u>
std_02_Tue_shift_C_st op_time		Standard work week shift_C_stop time, Tuesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_02_Tue_shift_C_stop_time	
std_03_Wed_shift_A_st art_time		Standard work week shift_A_start time, Wednesday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
		DS19.std_03_Wed_shift_A_start_time	
std_03_Wed_shift_A_st op_time		Standard work week shift_A_stop time, Wednesday. DS19.std_03_Wed_shift_A_stop_time	string, must be time as HH:MM:SS+00:00. (ISO 8601)
std 03 Wed shift B st		Standard work week shift_B_start time, Wednesday.	string, must be time as
art_time		DS19.std_03_Wed_shift_B_start_time	HH:MM:SS+00:00. (ISO 8601)
std_03_Wed_shift_B_st		Standard work week shift_B_stop time, Wednesday.	string, must be time as
op_time		DS19.std_03_Wed_shift_B_stop_time	HH:MM:SS+00:00. (ISO 8601)
std_03_Wed_shift_C_st		Standard work week shift_C_start time, Wednesday.	string, must be time as
art_time		DS19.std_03_Wed_shift_C_start_time	HH:MM:SS+00:00. (ISO 8601)
std_03_Wed_shift_C_st		Standard work week shift_C_stop time, Wednesday.	string, must be time as
op_time		DS19.std_03_Wed_shift_C_stop_time	HH:MM:SS+00:00. (ISO 8601)
std_04_Thu_shift_A_sta		Standard work week shift_A_start time, Thursday.	string, must be time as
rt_time		DS19.std_04_Thu_shift_A_start_time	HH:MM:SS+00:00. (ISO 8601)
std_04_Thu_shift_A_st		Standard work week shift_A_stop time, Thursday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
op_time		DS19.std_04_Thu_shift_A_stop_time	пп:мм:>>+00:00. (ISO 8601)



field name	req'd description unique field identifier (primary & calculated)	JSON data type example
std_04_Thu_shift_B_sta t_time	Standard work week shift_B_start time, Thursday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_04_Thu_shift_B_start_time	
td_04_Thu_shift_B_st p_time	Standard work week shift_B_stop time, Thursday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_04_Thu_shift_B_stop_time	
td_04_Thu_shift_C_sta :_time	Standard work week shift_C_start time, Thursday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_04_Thu_shift_C_start_time	
d_04_Thu_shift_C_st p_time	Standard work week shift_C_stop time, Thursday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_04_Thu_shift_C_stop_time	
d_05_Fri_shift_A_sta _time	Standard work week shift_A_start time, Friday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_05_Fri_shift_A_start_time	
d_05_Fri_shift_A_sto _time	Standard work week shift_A_stop time, Friday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_05_Fri_shift_A_stop_time	
d_05_Fri_shift_B_sta _time	Standard work week shift_B_start time, Friday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_05_Fri_shift_B_start_time	
td_05_Fri_shift_B_sto _time	Standard work week shift_B_stop time, Friday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
td_05_Fri_shift_C_sta	DS19.std_05_Fri_shift_B_stop_time	string, must be time as
t_time	Standard work week shift_C_start time, Friday. DS19.std_05_Fri_shift_C_start_time	HH:MM:SS+00:00. (ISO 8601)
td_05_Fri_shift_C_sto	Standard work week shift_C_stop time, Friday.	string, must be time as
_time	DS19.std_05_Fri_shift_C_stop_time	HH:MM:SS+00:00. (ISO 8601)
td_06_Sat_shift_A_sta :_time	Standard work week shift_A_start time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_A_start_time	
std_06_Sat_shift_A_st op_time	Standard work week shift_A_stop time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_A_stop_time	
td_06_Sat_shift_B_sta :_time	Standard work week shift_B_start time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_B_start_time	
td_06_Sat_shift_B_st p_time	Standard work week shift_B_stop time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_B_stop_time	
td_06_Sat_shift_C_sta :_time	Standard work week shift_C_start time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_C_start_time	
td_06_Sat_shift_C_st p_time	Standard work week shift_C_stop time, Saturday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_06_Sat_shift_C_stop_time	
td_07_Sun_shift_A_sta :_time	Standard work week shift_A_start time, Sunday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
	DS19.std_07_Sun_shift_A_start_time	
td_07_Sun_shift_A_st p_time	Standard work week shift_A_stop time, Sunday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
tal 07 Cum al-life D	DS19.std_07_Sun_shift_A_stop_time	atrice would be there are
td_07_Sun_shift_B_sta t_time	Standard work week shift_B_start time, Sunday.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
tal 07 Cum al-life D	DS19.std_07_Sun_shift_B_start_time	atrice and the first
td_07_Sun_shift_B_st p_time	Standard work week shift_B_stop time, Sunday. DS19.std 07 Sun shift B stop time	string, must be time as HH:MM:SS+00:00. (ISO 8601)
td_07_Sun_shift_C_sta	Standard work week shift_C_start time, Sunday.	string, must be time as
_time	DS19.std_07_Sun_shift_C_start_time	HH:MM:SS+00:00. (ISO 8601)
td_07_Sun_shift_C_st	Standard work week shift_C_stop time, Sunday.	string, must be time as
p_time	DS19.std_07_Sun_shift_C_stop_time	HH:MM:SS+00:00. (ISO 8601)
ubproject ID	Unique subproject identifier.	string, maxLength: 50
	DS19.subproject_ID	-



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-0-28, PARS Support, Revisions. v03.21, 2022-11-0-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



			Till 10
field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS20 schedule_calendar_excep tion			
description		This data set should be populated with the project's contractor IMS tool calendar exception data for the entire span of the project (not the contract). Exception day is limited to 3 shifts (A, B, and C) for breaks in between shifts, starting with shift A, half hour increments, and no overlaps. If more than 3 shifts, 3rd shift should be stretched to the last shift. There should be alignment between the BL and FC IMSs.	
calendar name	Х	Calendar name.	string, maxLength: 50
		DS20.calendar_name	
exception date	Х	Date of exception.	string, must be date as YYYY-MM-DD
		DS20.exception_date	
exception_work_day	Х	Exception is a work day (Y or N). If Y then all day is exception and shift times do not need to be provided. If N then provide shift times.	string, select from: Y, N
		DS20.exception_work_day	
exception_shift_A_star t_time		Exception shift_A_start time.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
r_ume		DS20.exception_shift_A_start_time	TII 1.WWW.33400.00. (130 8001)
exception_shift_A_stop time		Exception shift_A_stop time.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
_unie		DS20.exception_shift_A_stop_time	111 1.1VIIVI.36+00.00. (166 0001)
exception_shift_B_star		Exception shift_B_start time.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
<u> </u>		DS20.exception_shift_B_start_time	111 1.IVIIVI.SS+00.00. (ISS 0001)
exception_shift_B_stop time		Exception shift_B_stop time.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
_ume		DS20.exception_shift_B_stop_time	TII 1.IVIIVI.33+00.00. (130 8001)
exception_shift_C_star		Exception shift_C_start time.	string, must be time as HH:MM:SS+00:00. (ISO 8601)
r_ume		DS20.exception_shift_C_start_time	TII 1.IVIIVI.33700.00. (130 8001)
exception_shift_C_stop time		Exception shift_C_stop time.	string, must be time as
_ume		DS20.exception_shift_C_stop_time	HH:MM:SS+00:00. (ISO 8601)
subproject ID		Unique subproject identifier.	string, maxLength: 50
		DS20.subproject_ID	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release, v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release, v02.01, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release, v03.00, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-07, PM-30, Melvin Frank, Updated for release, v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release, v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS21 rates			
description		This data set should be populated with the project's contractor EVMS cost tool resource rates. Provide the contractor EVMS cost tool resource rates by WP WBS level, resource identifier, and applicable FYs. The data may be UCNI.	
resource ID	Х	Resource identifier.	string, maxLength: 50
		DS21.resource_ID	
EOC	X	EOC selection aligned with DS03.EOC: labor material subcontract ODC	string, select from: labor, material, subcontract, ODC
		DS21.EOC	
burden_ID		Burden identifier (or overhead key) from accounting system, used to calculate indirect rate.	string, maxLength: 50
		DS21.burden_ID	
type		Rate type: • D = direct rate • I = indirect rate	string, select from: D, I
		DS21.type	
rate_start_date	Х	Start date for which the rate is applicable.	string, must be date as YYYY-MM-DD
		DS21.rate_start_date	
rate_dollars	Х	Rate (dollars).	number, max. of 2 decimal places
		DS21.rate_dollars	
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release, v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release, v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release, v03.01, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-07, PM-30, Melvin Frank, Updated for release, v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release, v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	



field name	req'd	description	JSON data type
		unique field identifier (primary & calculated)	example
DS22 financial_calendar	r		
description		This data set should be populated with the project's contractor financial tool calendar for the entire span of the project (not the contract).	
calendar name	Х	Unique calendar name.	string, maxLength: 50
		DS22.calendar_name	
period_date	Х	Time-phased period end dates. The data should align with the contractor data-as-of date and the CPP_status_date. The delta between sequential dates should be a month. There should be no more than 12 period dates in a fiscal year. DS22.period_date	string, must be date as YYYY-MM-DD
period ID	Х	Period identifier. The data is >0, starting with 1 and increments by 1. DS22.period_ID	integer, min. value: 1, max. value: 600
revision		v01.00, 2022-07-19, PM-30, Melvin Frank, Updated for release v02.00, 2022-08-22, PM-30, Melvin Frank, Updated for release. v02.01, 2022-08-25, PM-30, Melvin Frank, Updated for release. v02.02, 2022-09-01, PARS Support, Minor revisions. v02.10, 2022-10-20, PARS Support, Revisions. v03.00, 2022-10-25, PM-30, Melvin Frank, Updated for release. v03.10, 2022-10-28, PARS Support, Revisions. v03.21, 2022-11-28, PARS Support, Revisions. v03.21, 2022-11-10, PM-30, Melvin Frank, Updated for release. v04.00, 2023-02-23, PM-30, Melvin Frank, Updated for release. v05.00, 2023-08-14, PM-30, Melvin Frank, Updated for release.	